



BC-800NM4 & BC-800NM Battery Chargers

Features

Conditioning Cycle

Provides built-in maintenance capability to maximise battery cycle life.

Status Indicators

'Charging', 'Ready', 'Rejected' (dead battery), 'Conditioning Cycle' and 'Power LED' indicators make the BC-800NM simple and easy to use

Intelligent Charging

- Optimizes the battery
- Battery can remain in the charger indefinitely
- Maintains battery at peak capacity

Rapid Charge Capability

Charges in less than 2 hours

BC-800NM4 & BC-800NM Specifications

Physical Characteristics

BC-800NM4

Product Dimensions: 13" (33cm) W x 1.7" (4.5cm)
H x 7" (17.8cm) D
Product Weight: 4lbs (1.5kg) without battery adapters
Shipping Dimensions: 11.5" (29.2cm)
W x 10.5" (26.7cm) H x 18.5" (47cm) D
Shipping Weight: 10lbs, 9oz (4.8kg) with battery
adapters, power supply, & rechargeable battery packs

BC-800NM

Product Dimensions: 3" (7.62cm) W x 3.5" (8.89cm)
H x 6" (15.24cm) D
Product Weight: 1lb, 6oz (0.62kg)
Shipping Dimensions: 7" (17.8cm) W x 4.5" (11.43cm)
H x 7" (17.8cm) D
Shipping Weight: 2lbs, 10oz (1.2kg) with rechargeable
battery pack & power supply

Material: ABS KJW fire retardant plastic, textured

User Environment

ESD: 8KV continuous contact discharge; 15KV from air
to all surfaces without contact

Humidity: 95% relative humidity (non-condensing)

Drop: Unit functions normally after 4ft./1.2m drop to
concrete

Storage Temperature: -40° to 122°F/-40° to 50°C

Operating Temperature: 32° to 122°F/0° to 50°C

Power Supply:

BC-800NM4 (Universal): 90V-230VAC, 50/60 Hz

Output: 15 VDC, 5A or 24 VDC, 4.5A

BC-800NM (Universal): 90V-230VAC, 50/60 Hz

Output: 15 VDC, 1.5A or 24 VDC, 1.3A

Safety Standards: Charger & power supply UL listed
(UL 1950), CSA Certified (C 22.2 No. 223); Compliant to
FCC part 15 Class A and CE Marking (Electromagnetic
Compatibility) Directive 89/336/EEC and Low Voltage
Directive 73/23/EEC; C15PR-22 Class B

Performance Characteristics

Rapid Charging: Charges batteries to 90+% capacity in
2 hours or less

Complete Charge: Completes 100% capacity charge in 4
hours or less

Conditioning: Completely discharges a battery and
automatically switches to charging mode

Maintenance Charge: Maintains the battery at optimum
capacity indefinitely

User Interface

Power LED: Indicates POWER to charging slot

Conditioning/Charging LED: Flashing indicates
discharging process

Reject LED: Flashing indicates faulty battery

Conditioning/Charging LED: Solid indicates battery pack
is being charged

Ready LED: Solid indicates battery charged

Ordering Information

BC-800NM

Single-Bay Charger for TR-1/700/800/825/RKP-4 with
USA power cord and BP-700NM

Catalog Number: PRD000070006

BC-800NME

Single-Bay Charger for TR-1/700/800/825/RKP-4 with
Euro power cord and BP-700NM

Catalog Number: PRD000070007

BC-800NM4

Four-Bay Charger for TR-1/700/800/825/RKP-4 with
USA power cord and BP-700NM

Catalog Number: PRD000070008

BC-800NM4E

Four-Bay Charger for TR-1/700/800/825/RKP-4 with
Euro power cord and BP-700NM

Catalog Number: PRD000070009

C800NM

Single-Bay Charger without Power Supply

Catalog Number: PRD000070000

CB800NM4

Docking Station, Four-Bay Charger

Catalog Number: PRD000070003

PS800NM4

Power Supply for Four-Bay Charger

Catalog Number: PRD000070004

PS-800NM

Power Supply for Single-Bay Charger

Catalog Number: PRD000070001

PC-UK

BC-800NM and BC-800NM4 UK Power Cord.

Catalog Number: 550024002

This specifications information is preliminary and is subject to change without notification.

Brand names mentioned are the property of their respective companies.