

Technical Data Sheet

Innovating the Future of Global Communications

LH-300


General Description

The LH-300 is a single-sided super lightweight headset for the ultimate in day-long comfort. Offering a noise-canceling microphone with a semi-rigid, fully adjustable boom for precise positioning. The high-quality, wide band, dynamic earphones are covered in a pliable material for superior fit, isolation, and frequency response.



Features

- · Fully rotating boom microphone positionable for right- or left-side use
- Boom mounted, noise-canceling microphone
- Soft, pliable ear cushions and headband pads



Order Information

Models

- LH-300-DM-A4F Single Side, Dynamic Mic, A4F
- LH-300-DM-A4M Single Side, Dynamic Mic, A4M
- LH-300-DM-A5M Single Side, Dynamic Mic, A5M
- LH-300-EM-i3.5 Single Side, Electret Mic, 3.5mm
- LH-300-DM-PT Single Side, Dynamic Mic

Accessories

- LH-WS Windscreen for LH Series 2 pcs
- LH-EC1 Foam Ear Cushion for LH Series 2 pcs
- LH-EC2 Supple Ear Cushion for LH Series 2 pcs
- LH-CC Clothing Clip for LH Series
- LH-SC Storage Case for LH Series
- LH-HBP Headband Pad for LH Series
- LH-HC Hygiene Covers for LH Series 10 pcs

For ordering information, contact your regional sales representative at www.rtsintercoms.com

Specifications

Headphor	ne	Sensitivity	<i>ı</i> :		
Туре:			Dynamic: -63 \pm 3.5 dB r	e:1V/Pa @ 1 kHz	
	Dynamic		Electret: -41 \pm 3.5 dB re	: 1V/Pa @1 kHz	
Impedance:		Operating	Voltage:		
	150 Ω ±20% @1kHz -		Electret Microphone: 2V	through 2.2K resistor	
	• LH-300-DM-A4F	Connector	r Туре:		
	• LH-300-DM-A4M		LH-300-DM-A4F		4-pin female XLR
	$300 \ \Omega \pm 20\%$ @1kHz -		LH-300-DM-A4M		4-pin male XLR
	 LH-300-DM-A5M 		LH-300-DM-A5M		5-pin male XLR
	• LH-300-DM-PT		LH-300-DM-PT		no connector
	• LH-300-EM-i3.5		LH-300-EM-i3.5		4 conductor
Sensitivity:					3.5mm
-	99 ± 4 dBSPL @ 1 kHz & 1 mW with B&K 4153 (150 Ω)	Physica	1		
	100 ± 4 dBSPL @ 1 kHz & 1 mW with B&K 4153 (300 Ω)	Weight:		headset weight	wearing weigh
Frequency F				(with cord)	(without cord
200 Hz – 10 kHz (-10 dB re. 1 kHz)			LH-300-DM-A4F	~5.2 oz (~147 g)	~2.6 oz (~74 g
Microphone			LH-300-DM-A4M	~5.2 oz (~147 g)	~2.6 oz (~74 g
Element Type:			LH-300-DM-A5M	~5.2 oz (~147 g)	~2.6 oz (~74 g
	Noise-Canceling Dynamic -		LH-300-DM-PT	~3.9 oz (~111 g)	~2.6 oz (~74 g
	• LH-300-DM-A4F		LH-300-EM-i3.5	~3.4 oz (~ 96 g)	~2.6 oz (~74 g
	• LH-300-DM-A4M	Cord Leng	gth:		
	 LH-300-DM-A5M 		6 ft. \pm 4 in. (1.8m \pm 10cr	m.) (measured from tip to	the earshell)
	• LH-300-DM-PT	Color:			
	Noise-Canceling Electret -		Black and Stainless Ste	el	
	• LH-300-EM-i3.5				
mpedance:					
•	Dynamic: 200 Ω				
	Electret: approx. 2.2 KΩ				
Frequency F	Response:				
	Dynamic: 200 Hz – 6500 Hz				
	Electret: 200 Hz – 10 kHz				
\sim					
Conne	ector Pinouts				



XLR-4F



XLR-4M

	Description	Color		Description	Color
Pin 1	Mic Low	Blue/Mic Shield	Pin 1	Mic Low	Blue/Mic Shield
Pin 2	Mic High	White	Pin 2	Mic High	White
Pin 3	Headphone Low	Black/Shield	Pin 3	Headphone Low	Black/Shield
Pin 4	Headphone High	Yellow	Pin 4	Headphone High	Yellow
Case		N/C	Case		NC

		Description	Color
	Pin 1	Mic Low	Blue/Mic Shield
	Pin 2	Mic High	White
	Pin 3	Headphone Low	Black/Shield
	Pin 4	Headphone High	Yellow
	Pin 5	Headphone 2 High	Red
1	Case	Inner Shield	N/C

XLR-5M

Т

Color

Т

The pigtail version comes without a connector. It is the customer's responsibility to install the proper connector		
Description	Color	
Microphone +	White	
Microphone -	Blue	

Description	000	
Microphone +	White	
Microphone -	Blue	
Microphone Shield	Inner Shield	
Speaker +	Yellow	
Speaker -	Black	
Speaker Shield	Outer Shield	





3.5mm plug			
	Description	Color	
Tip	Boom Side Headphone Signal	Red	
Ring 1	Non-Boorn Side Headphone Signal	Black	
Ring 2	Headphone and Mic Return	Shield	
Sleeve	Mic Signal	White	

Bosch Security Systems, Inc. | 12000 Portland Avenue South | Burnsville, Minnesota 55337 Website: www.rtsintercoms.com Form Number: F.01U.315.071 Rev 07 Date: April 2018



