



£



NEXT DAY DELIVERY
AVAILABLE

FREE STANDARD UK DELIVERY
ON ALL ORDERS OVER £100

INDUSTRY LEADING
CUSTOMER SERVICE

FREE TECHNICAL SUPPORT
FROM OUR TEAM OF EXPERTS

Categories

- Audio and data connectors
- Video and RF connectors
- Power connectors, distribution and batteries
- Connection panels and stageboxes
- Fibre optic cables, connectors and interfaces
- Cable assemblies, patchcords and leads
- Cables
- Cabling accessories and tools
- Bags and cases
- Racks and enclosures
- Rack accessories and hardware
- Lights, clocks, furniture, fittings and equipment supports
- Drives, memory, media, labelling and sound effects
- Microphones
- Radio Microphones
- Microphone supports, amplifiers, powering and accessories
- Headphones, headsets, earpieces, amplifiers and wireless systems
- Hearing protection and noise control
- Record, replay and radio receivers
- Audio interfacing
- Video interfacing, processing, monitoring and camera accessories
- Audio mixers and processing
- Amplification
- Loudspeakers and audio monitoring
- Test and measurement
- Communications, conferencing and datacoms

By brand

Index

New products

Special offers

Clearance list

Remainder list

Pr... Video interfacing, proce... Hum blockers ... LEN VIDEO FILTERS - MEDICAL GRADE... LEN L4KGI03 VIDEO ISOLATOR Galvanic video a...

LEN L4KGI03 VIDEO ISOLATOR Galvanic video and ground path isolator, high voltage, 4K/12G UHD SDI

Datasheet Print/PDF Ask a question

Stock code

90-6159

Brand

LEN

Model number

L4KGI03



LEN VIDEO FILTERS - MEDICAL GRADE - SD, HD, 3G, 4K/12G SDI ground isolation

These LEN ground isolators use broadband high-pass filters to provide complete galvanic isolation of DC currents between two pieces of equipment, whilst permitting the full bandwidth of the SDI signal to pass, thus avoiding problems of signal distortion and operator shocks caused by a voltage difference. This method outperforms broadband transformers for SDI signals. Both signal and ground paths between equipment are isolated, there is no distortion of the signal. They are suitable for ASI format.

These medical grade isolators offer a higher breakdown voltage for medical grade applications, and are available both constructed in ABS boxes with mounting flanges and as 'barrel' versions, with or without a mounting flange. For non-medical grade isolators see [LEN VIDEO FILTERS - SD, HD, 3G, 4K/12G SDI ground isolation](#).

Common specifications are as follows. Input and output impedance: 75 ohms. Return loss: Better than 20dB.

Model	Bandwidth(1)	Breakdown Voltage(1)
LHDF03	0.5 MHz to 1485 MHz, - 0.25dB	4kV
L3GF03	0.5 MHz to 3000 MHz, - 0.25dB	4kV
LHDGI03	0.5 MHz to 1485 MHz, - 0.25dB	4kV
L3GGI03	0.5 MHz to 3000 MHz, - 0.25dB	4kV
L4KGI03	0.5 MHz to 12000 MHz, - 0.25dB	4kV

Note 1: These are minimum values.



L3GF03, LHDF03 - High Breakdown Voltage, Encapsulated Enclosure

L3GF03 may be used with 3G, HD or SD SDI signals while the LHDF03 may be used with HD or SD SDI. These have a very high breakdown voltage, as required for medical grade applications. They are constructed in ABS boxes with mounting flanges, fitted with two female BNC connectors.

Dimensions: 50 x 35 x 15 (l x w x h) mm excluding mounting flanges, 68mm length including flanges. Weight: 32g.









LHDGI03, L3GGI03, L4KGI03 - High Breakdown Voltage, In-line 'Barrel' Type, with mounting flange for through panel fitment

L4KGI03 is for use with full 12G/4K UHD SDI video and all lower standards including 6G, 3G, HD and SD SDI. L3GGI03 may be used with 3G, HD or SD SDI signals while the LHDGI03 may be used with HD or SD SDI. These have a very high breakdown voltage, as required for medical grade applications. They are built in cylindrical plastic (for isolation) enclosures, fitted with a BNC connector at each end. An industry-standard size mounting flange is fitted at one end.

Dimensions: 30 x 20 (l x diameter) mm, mounting flange 31 x 26 mm. Weight: 37g.

Optional accessories: [LMPG01](#) rack frame is a 1U 19-inch full width panel, finished in black, punched to take sixteen isolators mounted from the rear by means of the mounting flanges, so that the BNC connectors are on either side of the rack. LMPG02 rack frame is a 1U 19-inch half width panel, punched to take eight isolators, mounted in the same way as the full width panel.

Description	Price £ ex. VAT	Add to basket Delivery
 <p>LEN LHDF03 VIDEO ISOLATOR Galvanic video and ground path isolator, high voltage, HD SDI</p> <p>Stock code: 90-6155</p> <p>Please login for stock availability and lead times.</p>	£286.70	1
 <p>LEN L3GF03 VIDEO ISOLATOR Galvanic video and ground path isolator, high voltage, 3G HD SDI</p> <p>Stock code: 90-6156</p> <p>Please login for stock availability and lead times.</p>	£344.00	1
 <p>LEN LHDGI03 VIDEO ISOLATOR Galvanic video and ground path isolator, high voltage, SD HD SDI</p> <p>Stock code: 90-6157</p> <p>Please login for stock availability and lead times.</p>	£286.70	1
 <p>LEN L3GGI03 VIDEO ISOLATOR Galvanic video and ground path isolator, high voltage, 3G SD HD SDI</p> <p>Stock code: 90-6158</p> <p>Please login for stock availability and lead times.</p>	£344.00	1
 <p>LEN L4KGI03 VIDEO ISOLATOR Galvanic video and ground path isolator, high voltage, 4K/12G UHD SDI</p> <p>Stock code: 90-6159</p> <p>Please login for stock availability and lead times.</p>	£753.00	1
 <p>LEN LMPG01 RACK PANEL For 16x video isolators, 1U</p> <p>Stock code: 90-6149</p> <p>Please login for stock availability and lead times.</p>	£74.71	1



About Canford
About Canford
Meet the team

Orders & delivery
Ordering information
Delivery & Returns

Resources
TechZone
RoHS & WEEE

Website information
Copyright & security
Conditions of website use

Canford Audio Limited, Crowther Road, Washington, NE38 0BW, UK

UK Sales 0191 418 1122
International Sales +44 191 418 1133

Canford Audio Limited is registered in England and Wales
Company registration no: 1385727
VAT no: GB 660116371



Cookie consent

This site uses cookies to store information on your computer. By continuing we assume your permission to store cookies, as detailed in our [privacy policy](#).

